hp LaserJet
1300 series

hp LaserJet 1300/n printer

Promote your business effectively with the HP LaserJet 1300 series printer. With this network capable, flexible and compatible black and white printer you can produce business documents reliably and its compact desktop design fits most work spaces.

A very reliable black and white printing solution for business professionals working in any size office, who need a fast and flexible personal printer with network capabilities and additional paper handling for their business documents.

The efficient, reliable way to produce great looking, high quality documents quickly and easily.
- No wait for the printer to warm up as an instant-on fuser ensures the first page prints in just 8 seconds and print speeds of up to 19 ppm (A4).
- HP LaserJet printing technology (All-in-One cartridge and charging rollers) ensures a safer environment with no appreciable ozone emissions and no manual maintenance required.
- An HP Embedded Web Server provides direct access to the printer via a standard web browser, and allows full control to configure device settings and e-mail alerts remotely.

High performance laser printing you can expand easily to meet your business needs.
- Set up quickly and connect easily using the USB or parallel ports. Use the flexibility of the LIO port by sharing the printer through the HP Jetdirect LIO internal print server* or add a wireless external print server to extend your printing options.
- Use the DIMM slot to add more memory, fonts, or third-party solutions.
- Add a 250-sheet tray to the existing 250-sheet tray and 10-sheet input slot for greater media input capacity.
- Supports a wide range of media types and sizes.

Get the most from compatibility in any environment and support for a range of operating systems.
- Compatible in most environments supporting HP PCL 5e, PCL 6 and HP Postscript level 2 emulation.
- Supports many operating systems including Windows® 95, 98 and higher, Mac® OS 8.6, 9.x and OS X, Linux, UNIX®, and MS-DOS.
- Take the headache out of managing your printer and supplies with the Embedded Web Server and e-labels in Smart print supplies for easy status monitoring and printer support.

hp LaserJet 1300

*Standard with HP LaserJet 1300n.

hp LaserJet 1300n

hp LaserJet 1300 series

technical specifications

print technology	Monochrome Laser			
print speed	Up to 19 ppm First page out: 8 sec instant-on fusing technology for no warm-up time - from warm or cold start. (Exact speed varies depending on the system configuration, software program and document complexity)			
processor	133 MHz; Motorola Coldfire			
memory	16 MB using Memory Enhancement technology (MEt). Expandable to 80 MB through one industry-standard DIMM slot			
print quality	1200 x 1200 dpi			
printer languages	HP PCL 6, HP PCL 5e, HP Postscript level 2 emulation			
economical printing levels	Economode (saves up to 50% toner), immediate return to power-safe mode after each print job due to instant-on fuser technology (saves electricity), N-up printing and manual duplex (saves paper)			
typefaces/fonts	HP PCL 6: 45 scalable True Type fonts built-in, HP Postscript level 2 emulation: 35 scalable True Type fonts built-in			
print margins (A4)	Top: 2.7 mm; left: 2.4 mm; right: 3.8 mm; bottom: 5 mm			
duty cycle	Up to 10,000 pages per month			

media handling

	input	capacity	weight	size
	Standard Tray:	up to 250 sheets, 30 envelopes	60 g/m² to 105 g/m², using the standard output bin; 60 g/m² to 163 g/m², using the straight through media path	A4, A5, Letter, Legal, Executive, B5 (JIS), B5 (ISO), C5, DL, Monarch, Com-10, 76 x 127 mm to 216 x 356 mm
	Priority Tray:	10 sheets	60 g/m² to 105 g/m², using the standard output bin; 60 g/m² to 163 g/m², using the straight through media path	A4, A5, Letter, Legal, Executive, B5 (JIS), B5 (ISO), C5, DL, Monarch, Com-10, 76 x 127 mm to 216 x 356 mm
	Optional 2nd Paper Tray:	250 sheets	60 g/m² to 105 g/m²	A4, A5, Letter, Legal, Executive, B5 (JIS), B5 (ISO), C5, DL, Monarch, Com-10, 76 x 127 mm to 216 x 356 mm
	output:	sheets: 125, envelopes: 30, transparencies: 100		
	duplex printing: manual			

media types	Paper, cardstock, envelopes, heavy media, labels, transparencies
interface and connectivity	Standard: HP LaserJet 1300 printer: USB port (2.0 compliant), IEEE 1284-compliant bi-directional parallel LIO adapter, HP LaserJet 1300n printer: HP Jetdirect 200m LIO print server, USB (2.0 compliant) Optional: HP Jetdirect internal print servers; HP Jetdirect external print servers; HP wireless print servers; Bluetooth wireless printer adapter
operating systems compatibility	Microsoft® Windows® 98, 2000, Me, and XP; Windows 95, NT 4.0 (SP3) and XP 64-bit (print driver only); Mac® OS 8.6, 9.x, Mac OS X and later, MS-DOS, Linux and UNIX®.
network operating systems compatibility	Microsoft® Windows® 98, NT 4.0, 2000, Me, XP, XP 64-bit; Mac® OS 8.6 and later; optional: Novell® NetWare 4.2, 5.x, 6; Red Hat Linux 6.x and later; SuSE Linux 6.x and later; HP-UX 10.20, 11.x; Solaris™ 2.5x, 2.6, 7, 8; IBM® AIX 3.2.5 and later; MPE-iX.
minimum system requirements	Operating system requirements as recommended by the operating system vendor plus free hard disk space (140 MB for full installation, 10 MB for print drivers only), CD-ROM disk drive, USB or parallel port Macintosh®: Power PC G3 or higher, OS 8.6 and 9.X - 64 MB RAM, OS X - 128 MB RAM, 15 MB free hard disk space, CD-ROM drive
standard software	HP Printer Software on CD-ROM includes HP Installer/uninstaller, drivers - HP PCL 5e, HP PCL 6, HP Postscript level 2 emulation, HP Toolbox for diagnostic status and configuration, Embedded Web Server, help, documentation.
control panel	Simplified control panel with combined "Go" and "Cancel" job button, and three LEDs for status.
power requirements	Input voltage 110-127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)
power consumption	0 watts (off), 7 watts maximum (powersave/standby), 320 watts maximum (printing)
dimensions (w x d x h)	Out of package: 415 x 486 x 241 mm; packaged: 500 x 400 x 450 mm
weight	Out of package: 8.6 kg
printer management	HP Web Jetadmin, HP toolbox or HP embedded web server
operating environment	Environmental Ranges: Operating temperature: 10 to 32.5° C; operating humidity: 20 to 80% RH (non-condensing); recommended operating humidity: 20 to 80% RH; recommended operating temperature: 10 to 32.5°C; storage temperature: 0 to 40°C, storage humidity: 10 to 80% RH, noise level per ISO 9296: sound power LwAd: 6.3 B(A) (printing), sound pressure LpAm: 57 dB(A) printing (operating position), 49 dB(A) printing (bystander position)
certifications	Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN60950-IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV- EN60950-IEC 60825-1), Hungary (MEEI- IEC 60950-IEC 60825-1), Lithuania (LS- IEC 60950-IEC 60825-1), Poland (B Mark- IEC 60950-IEC60825-1), Russia (GOST- R50377), Slovakia (IEC 60950-IEC60825-1), Slovenia (SQI- IEC 60950-EN60825-1), South Africa (IEC 60950-IEC60825-1). Energy Star®
warranty	1 year standard bench repair and return (HP/dealer). Upgrade standard warranty with optional HP Supportpacks to 3 years (not included)